



207

**WHEN PERFORMANCE MATTERS,
207 DELIVERS.**



REMOVAL TIME (DAYS):
13 (INDOOR) / 10 (OUTDOOR)

TEMPERATURE RESISTANCE:
212°F - 30 MIN

TOTAL THICKNESS:
0.13MM / 5.15MILS

ADHESION TO STEEL:
5.9N/25MM / 21 OZ/IN

TENSILE STRENGTH:
79N/25MM / 18 LBS/IN

DESCRIPTION:

Clean edges and effortless removal, resistant to UV, humidity, and heat up to 212°F (100°C) without lifting, curling, or leaving residue. With smooth unwind and flexible fit, 207 is designed for speed and precision, perfect for clean finishes on delicate or detailed work.

313

**READY FOR THE TOUGHEST JOBS:
THIS IS 313.**



REMOVAL TIME (DAYS):
15 (INDOOR) / 14 (OUTDOOR)

TEMPERATURE RESISTANCE:
248°F - 60 MIN

TOTAL THICKNESS:
0.15MM / 5.79MILS

ADHESION TO STEEL:
5.9N/25MM / 21 OZ/IN

TENSILE STRENGTH:
91N/25MM / 20 LBS/IN

DESCRIPTION:

Unbeatable hold, sharp lines and clean removal even in heat, humidity, or heavy-duty prep cycles. Waterproof, high-temp resistant and built to last, 313 is the pro masking tape that never quits. Designed to perform with textured surfaces and thick coatings, it ensures full contact and flawless results.

316

**MEET THE 316:
NOTHING STICKS LIKE THIS.**



REMOVAL TIME (DAYS):
20 (INDOOR) / 15 (OUTDOOR)

TEMPERATURE RESISTANCE:
248°F - 60 MIN

TOTAL THICKNESS:
0.15MM / 5.79MILS

ADHESION TO STEEL:
5.9N/25MM / 21 OZ/IN

TENSILE STRENGTH:
92N/25MM / 21 LBS/IN

DESCRIPTION:

Unmatched adhesion, resistance and total control: 316 is built for the toughest masking jobs on any surface, in any condition. From solvents and high heat to textured curves and thick coatings, it delivers flawless results with clean removal and zero compromise. This is the ultimate choice for pros who demand perfection.

VIBAC®

MASKING TAPE MANUFACTURER

